

05/27/99
JCS95 U.S. PTO

CALIFORNIA OFFICE
1010 EL CAMINO REAL
MENLO PARK, CA 94025
TELEPHONE (650) 325-5800
FACSIMILE (650) 325-6606

LAW OFFICES
SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC
2100 PENNSYLVANIA AVENUE, N.W.
WASHINGTON, DC 20037-3213
TELEPHONE (202) 293-7060
FACSIMILE (202) 293-7860

c490 U.S. PTO
09/320643
05/27/99

JAPAN OFFICE
TOEI NISHI SHIMBASHI BLDG. 4F
13-5 NISHI SHIMBASHI 1-CHOME
MINATO-KU, TOKYO 105, JAPAN
TELEPHONE (03) 3503-3760
FACSIMILE (03) 3503-3756

May 27, 1999

Ass't Commissioner of Patents
Washington, D.C. 20231

ATT: APPLICATION BRANCH

Re: U.S. Application of Marco PIVA and Maurizio BIANCHI for "APPARATUS
AND METHOD FOR READING AN OPTICAL CODE"
Our Ref: Q-54188

Sir:

Attached hereto is the application identified above including the claim to
priority, executed Declaration, Assignment, Preliminary Amendment,
Information Disclosure Statement and formal drawings containing Figures 1-
06. The Government filing fee is calculated as follows:

Total claims	35 - 20 = 15	x \$18(09) =	270.00
Independent Claims	02 - 03 = 00	x \$78(39) =	
Base Fee (\$760.00/\$380.00)			760.00
Assignment Recordal Fee (\$40.00)			40.00
Multiple Dependent Claim Fee (\$260./\$130.)			
Foreign Language Filing Fee (\$130.00)			
TOTAL FILING FEE			1070.00

Attached is a check in the amount of \$1070.00 for the initial filing of the
application, excess claim fee and recordal of the Assignment. The Patent
Office is authorized to charge or credit any difference or overpayment to
Deposit Account No. 19-4880. The Commissioner is hereby authorized to
charge any fees under 37 C.F.R. §§ 1.16 and 1.17 which may be required
during the entire pendency of the application to Deposit Account No. 19-
4880.

Priority is claimed for this application from European Appl. 98830336.8
filed June 1, 1998. The priority document will be submitted in due course.

Respectfully submitted,



Robert V. Sloan
Reg. No. 22,775

RVS:jlq
Attachments:

PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the Application of

Marco PIVA et al.

Filed: May 27, 1999

For: APPARATUS AND METHOD FOR READING AN OPTICAL CODE

Ass't Commissioner of Patents
Washington, D.C. 20231

ATT: APPLICATION BRANCH

Sir:

PRELIMINARY AMENDMENT

Prior to the examination of the above identified application and to the calculation of the fees, please amend this application as follows:

IN THE CLAIMS:

Claim 9, line 1, change "claims 3 and 8" to -- claim 8 --.

Claim 10, line 1, change "claims 2 and 8" to -- claim 2 --.

Claim 14, line 1, change "claims 2 and 13" to -- claim 2 --.

Claim 19, line 1, change "any of the preceding claims" to -- claim 1 --.

Claim 35, line 1, change "claims 32 to 34" to -- claim 32 --.

PATENT APPLICATION

REMARKS

The above claims have been amended to delete the multiple dependencies therein.

An early and favorable action on the merits is respectfully requested.

Respectfully submitted,



Robert V. Sloan
Reg. No. 22,775

RVS:jlq

SUGHRUE, MION, ZINN,
MACPEAK & SEAS, PLLC
2100 Pennsylvania Avenue, N.W.
Washington, D.C. 20037-3202
(202) 293-7060 / Fax: (202) 293-7860

Date: May 27, 1999

Att'y Docket No: Q-54188

An apparatus and method for reading an optical code**DESCRIPTION**

This invention relates to an apparatus and a method for reading an optical code. More particularly, the invention
5 relates to an apparatus and a method for reading an optical code within a preset distance range.

As is known, optical codes can be read by means of either stationary or portable reading apparatus. In either cases, the apparatus include a casing with a reading window
10 through which a means of illuminating a code to be read, and a means of reading the image of the code being read by detecting light scattered therefrom and converting it to electric signals, are both arranged to act. The detection means for converting the light signal to an electric signal
15 may be of different types; in general, a so-called CCD (Charge-Coupled Device) is used which comprises an array of a very large number of light-sensitive elements.

Reading apparatus of the above-described type have a drawback in that they can only provide a correct reading of
20 the optical codes within a limited distance range; this restricts substantially their applicability.

A problem to be solved in code reading as effected by a human operator and in automatic object sorting and handling systems, is that of identifying and classifying with a
25 single apparatus objects wherein the distance between the reading apparatus and the optical code can considerably vary. In this situation, the use of an apparatus as above described is disadvantageous, since the apparatus is not always capable of correctly focusing on the object codes to
30 be identified.

The underlying technical problem of this invention is that of enabling proper reading of optical codes placed at varying distances within a broad range of distances, using an apparatus of simple and low-cost construction.

Thus, the present invention provides, according to a first aspect thereof, an optical code reading apparatus which comprises:

- a casing;
- 5 - a reading window open into the casing;
- an illuminating means, housed within the casing, and arranged to act on an optical code to be read through the reading window;
- a detection means, housed within the casing and
10 responsive to light scattered from the illuminated optical code into the casing through the reading window;
- an objective lens having an optical axis, the objective lens being housed within the casing between the reading window and the detection means, and being located to pick
15 up light scattered from the illuminated optical code and project the picked-up light onto the detection means, wherein the detection means comprises a plurality of light-sensitive elements capable of converting said light to electric signals representing the light image,
20 characterized in that the illuminating means comprises a first array of light sources which are active in a first illumination configuration, and at least a second array of light sources which are active in at least a second illumination configuration different from the first.
- 25 Thus, an apparatus for reading remotely placed optical codes is provided which is capable of reading a code from a fixed position as well as within a broad range of distances.

For this purpose, the apparatus of the invention has a
30 field depth which is considerably greater than that of conventional reading apparatus, and is therefore particularly suitable for reading optical codes within a broad range of distances. The improved field depth is

achieved by providing the reading apparatus with a plurality of arrays of light sources which can be selectively activated to define a plurality of different illumination configurations, such that the optical code can
5 be illuminated and focused in an optimum manner at any values of the distance of the code from the reading apparatus.

Advantageously, the first array of light sources comprises a plurality of light source pairs, each pair in turn
10 comprising respective light sources symmetrically arranged with respect to the optical axis of the objective lens and aligned along a substantially perpendicular direction to said optical axis, said light sources lying in a first emission lay intersecting the optical axis and the light-
15 sensitive elements of the detection means. This allows each portion of an optical code being illuminated by the first array of light sources to be projected through the objective lens onto the light-sensitive elements, regardless of the distance between the optical code and the
20 reading apparatus, thereby to detect the light scattered from the code and convert it to electric signals.

Advantageously, the plurality of light source pairs comprises a pair of outward sources disposed in an offset position from the optical axis of the objective lens by an
25 angle α , and a pair of inward sources disposed in an offset position from the optical axis of the objective lens by an angle β , smaller than the angle α . Even more advantageously, the angle α is in the range of about 15° to about 18° , and the angle β is in the range of about 3° to
30 about 6° . In this way, the whole optical code can be suitably illuminated along its extension, even when placed at a considerable distance away from the reading apparatus.

In a specially advantageous embodiment, the apparatus of the invention further comprises a means for confining the
35 light beam from the first array of light sources within a predetermined reading area. Preferably, this means

comprises a ring-shaped masking element associated with the casing at the location of the reading window and having a substantially straight inward edge, set at an angle substantially equal to α with respect to the optical axis of the objective lens. As such, a confined light beam can be obtained which has a well defined shape and an extension substantially equal to that of the vision field of the detection means; this contributes to ensuring optimum illumination of the whole optical code at any values of distance between code and reading apparatus, thereby increasing the reading reliability.

The aforementioned advantages are also achieved by the provision, in the reading apparatus, of a holder element for the plurality of light source pairs which is formed with respective seats for said light sources, said seats having respective side walls shaped to confine the light beam from each source within the predetermined reading area. Advantageously, said side walls also function to screen off the detection means, thereby preventing any spurious rays issued from one of the light sources or reflected from a protective glass pane covering the reading window in the casing, from interfering with the scattered light from the code and therefore affecting the reading.

According to one embodiment of the invention, the detection means comprises a linear CCD. In this case, the responsive region of the detection means is represented by a line lying on the aforesaid first emission lay.

Advantageously, the apparatus of the invention further comprises a means for widening the emission angle of the light beam from the first array of light sources along the direction of alignment of said first array of light sources, and narrowing the emission angle of the light beam from the first array of light sources along the perpendicular direction to the first emission lay. Preferably, this means comprises a pair of converging lenses housed within the casing at symmetrical locations

with respect to the optical axis of the objective lens between the first array of light sources and the reading window. Thus, these lenses will widen and flatten the light beam from the first array of light sources to give it a comparable shape to that of the responsive region of the detection means, thereby improving the reading reliability.

Advantageously, the second array of light sources comprises a plurality of second light sources having a lower light intensity than the sources in the first array of light sources. These sources are intended for illuminating the optical code when the latter locates closer to the reading apparatus.

Advantageously, the second light sources are housed within the casing symmetrically with respect to the optical axis of the objective lens so as to be aligned to one another in a second emission lay, different from the first one. Preferably, the second emission lay is lower than the first emission lay and the second light sources are housed within the casing centrally with respect to the first array of light sources. The peculiar layout of the second light sources ensures optimum illumination of the code even at near-zero distance of the code from the reading apparatus.

In this case, the light beam issuing from the first array of light sources would have a minimum of light intensity at the central area, because of the gap existing between the two inward light sources in the first array of light sources wherein the objective lens is placed, and a maximum of light intensity at the peripheral areas, thus impairing proper acquisition of the code image. This problem is overcome by activating the second array of light sources; when activated, these light sources will mainly illuminate the above-mentioned central portion, thereby optimizing the overall illumination along the whole optical code.

Preferably, the first array of light sources comprises two pairs of discrete plastics LEDs, and the second array of

light sources comprises four SMD plastics LEDs.

The transition from one illumination configuration to the other (and hence activating the light sources in the second array) is effected according to an operational parameter
5 indicating the conditions of the reading operation.

In a first embodiment, the apparatus of this invention comprises a means for measuring the distance of the optical code to be read from the reading apparatus, and a means for activating said first and at least second arrays of light
10 sources according to the distance measured.

Thus, the operational parameter, whereby a decision is made as to whether the illumination configuration should be changed, is the distance between the optical code to be read and the reading apparatus. The reading apparatus
15 preferably comprises a device for measuring the distance (e.g. of the modulated laser light type as disclosed in Patent Application EP-A-0652530 by this Applicant) which is operatively linked to a microprocessor adapted to process the light scattered from the illuminated code to calculate
20 the distance value from the code, so as to select an optimum illumination configuration from a plurality of preset illumination configurations.

In a second embodiment, the apparatus of this invention comprises means for detecting the light intensity outline
25 of the scattered light from the optical code, a means for comparing this outline with a reference outline, and a means for activating said first and at least second arrays of light sources according to the difference between the detected outline and the reference outline. The operational
30 parameter whereby a decision is made as to whether to change the illumination configuration is, therefore, the light intensity outline of the code. The reading apparatus comprises, in particular, an envelope extractor, of a type known, which is operatively linked to a control unit
35 arranged to compare the of light intensity outline

scattered from the code with the reference outline, and accordingly select an optimum illumination configuration from a plurality of preset illumination configurations.

In a preferred embodiment, the apparatus of this invention
5 advantageously includes a means of decoding the optical code. Preferably, the apparatus further includes a means of activating said first and at least second arrays of light sources according to the results of decoding attempts. The operational parameter whereby a decision is made as to
10 whether the illumination configuration should be changed is, in this case, the number of unsuccessful decoding attempts made.

Preferably, the means for activating said first and at least second arrays of light sources comprises a
15 microprocessor, the apparatus further including a means of amplifying the electric signals generated by the detection means and means of converting the amplified electric signals to digital signals to be delivered to the microprocessor. In particular, the microprocessor inspect
20 the readings that fail to produce a decoding, class them, and accordingly select an optimum illumination configuration from a plurality of preset illumination configurations.

According to a preferred embodiment, the apparatus of the
25 invention includes a means of varying the amplification level of the electric signals generated by the detection means. In this way, the electric signals generated by the detection means can be digitalized even when they are too weak (such as because generated from a code located on a
30 far surface and/or having low contrast) or too strong (such as because generated from a code located on a near surface and/or having high contrast).

Preferably, the conversion means comprises a main digitalizer having a preset sensitivity and an auxiliary
35 digitalizer whose sensitivity is higher than that of the

main digitalizer. Advantageously, the two digitalizers are complementary ones; in fact, the main digitalizer is characterized by low signal distortion and is specially effective to digitalize signals having a wide dynamic range (e.g., for bar codes, signals wherein the difference in voltage level between the bar element and the space element is large), while the auxiliary digitalizer is specially effective to digitalize signals having a dynamic range which may be quite narrow, although with a higher signal distortion. Thus, the electric signals generated by the detection means in the different operative conditions in which the reading is carried out can be correctly digitalized, thereby improving the performance level of the reading apparatus.

According to a second aspect, this invention provides a method of reading an optical code by an apparatus comprising a means of illuminating an optical code to be read and means of detecting light scattered from the illuminated optical code, which method comprises the following steps:

- a) illuminating an optical code to be read so as to define a read scan;
- b) picking up the light scattered from the illuminated optical code on the detection means;
- c) converting the picked-up light to electric signals representing the light image;

characterized in that step a) of illuminating the optical code in turn comprises the following steps:

a1) acquiring an operational parameter indicating specific conditions of the reading operation;

a2) activating, according to the acquired operational parameter, a first array and/or at least a second array of light sources so as to illuminate the code according to

respective preset illumination configurations.

- The method of the invention advantageously enables an optimum illumination configuration to be selected to suit specific conditions of operation, thereby enhancing the reliability of the reading carried out.

In a first embodiment of the inventive method, step a1) of acquiring the operational parameter comprises a step of measuring the distance of the code to be read from the reading apparatus.

- 10 In a second embodiment of the inventive method, step a1) of acquiring the operational parameter comprises the following steps:

- detecting a light intensity outline of the scattered light from the optical code;

- 15 - comparing said outline with a reference outline;

- controlling the emissions from the light sources in the first and/or second arrays of light sources according to the difference between the detected outline and the reference outline.

- 20 In a specially advantageous embodiment of the method according to the invention, the operational parameter whereby a decision is made as to whether the illumination configuration should be changed is the number of unsuccessful decoding attempts.

- 25 Further features and advantages of this invention will be better understood from the following detailed description of a preferred embodiment thereof, given with reference to the accompanying drawings. In the drawings:

- 30 Figure 1 is a perspective view of an internal card of an optical code reading apparatus according to the invention with the construction elements of the apparatus mounted thereon;

Figure 2 is a front view of the card shown in Figure 1;

Figure 3 is a side view of the card shown in Figure 1;

Figure 4 is a top plan view of the card in Figure 1, with a ring-shaped masking element associated with one end thereof
5 to confine a light beam within a predetermined reading area;

Figure 5 is an enlarged exploded view of a portion of the card shown in Figure 4;

Figure 6 is a diagram exemplifying the optical code reading
10 method of this invention.

Shown at 1 in the drawing figures is a holder card intended for installation inside a casing (not shown) of an optical code reading apparatus (not shown). The casing is formed of lower and upper shells which can be conventionally joined
15 together into an enclosure capable of screening off any light rays other than those belonging to the reflected image of the optical code.

Throughout this description and the appended claims, the term "optical code" is used to indicate a code (such as a bar code, a two-dimensional code, or the like) adapted to
20 univocally identify the objects that bear it. In particular, reference will be made herein to bar codes for the sake of clarity.

As shown in Figures 1 to 5, the holder card 1 comprises a
25 front portion 1a intended to be facing the optical code to be read, in operation of the reading apparatus, and a back portion 1b. The front portion 1a is provided with an illumination means 3 adapted to illuminate the optical code through a reading window (not shown) which is formed
30 through the reading apparatus casing at the free end of the front portion 1a of the holder card 1. The back portion 1b is provided with a detection means 4 adapted to detect light scattered from the illuminated optical code and

passed to the casing interior through the reading window for converting this light to electric signals representing the light image.

Preferably, the detection means 4 comprises a linear type of CCD sensor 5, itself comprising an array formed of a very large plurality of individual light-sensitive elements 5a (Figure 4). Alternatively, the detection means 4 could comprise matrix or CMOS sensors; in any case, a responsive region 4a to the light scattered from the optical code (which region would be a line where a linear CCD is utilized) is defined on the detection means 4.

The illumination means 3 comprises a first array of light sources 6 (hereinafter also referred to as the main illuminators) and a second array of light sources 7 (the auxiliary illuminators) interposed between the first array of light sources 6 and the reading window. The first array of light sources 6 specifically comprises four discrete plastics LEDs, exhibiting high properties of light intensity and directivity, which have a diameter of about 5 mm and are housed in respective seats 6a formed in a holder element 8 made of a plastics material and mounted on the holder card 1 at the front portion 1a.

The holder element 8 is formed centrally with a seat 9a for receiving an objective lens 9 arranged to pick up light scattered from the illuminated optical code and project this light onto the detection means 4. The objective lens 9 has an optical axis Z which is substantially coincident with a longitudinal centerline of the holder card 1.

The LEDs 6 are positioned on the holder 8 symmetrically with respect to the optical axis Z of the objective lens 9; they are also aligned along a direction X which is perpendicular to said optical axis Z, thereby to define a first emission lay X-Z intersecting the optical axis Z and the responsive region 4a of the light-sensitive elements 5a. In particular, the LEDs 6 comprise a pair of outward

LEDs 61 disposed in an offset position from the optical axis Z of the objective lens 9 by an angle α within the range of about 15° to about 18°, and a pair of inward LEDs 62 disposed in an offset position from the optical axis Z of the objective lens 9 by an angle β within the range of about 3° to about 6°.

The seats 6a have opposite side walls 10 which are shaped to confine the light beam issuing from each LED 6 within a predetermined reading area. For the same purpose, the reading apparatus of the invention includes a ring-shaped masking element 11, generally made of a rubber, which is associated with the casing, at the front portion 1a of the holder card 1, and provided with a straight inner edge 12, set at an angle with respect to the optical axis Z of the objective lens 9, which is substantially the same as the angle α .

The holder element 8 is also provided with a pair of converging lenses 13 received in respective seats 13a formed in the holder element 8, between the seats 6a for the LEDs 6 and the reading window, at symmetrical locations with respect to the optical axis Z; the lenses 13 are designed to reduce the emission angle of the light beam issuing from the LEDs 6 in a direction Y perpendicular to the first emission lay X-Z, and to increase it in the direction X.

The second array of light sources 7 comprises four SMD plastics LEDs of lower light intensity and directivity than the LEDs 6; these LEDs 7 are aligned directly on the holder card 1 at central and symmetrical locations with respect to the optical axis Z of the objective lens 9, and define a second emission lay which is lower than and parallel to the first one.

The reading apparatus of the invention further includes a means of acquiring an operational parameter indicating specific conditions of the reading operation, according to

which parameter a microprocessor (not shown) will decide about the light sources to be activated. In a first embodiment, not shown, this means comprises a device for measuring the distance of the code to be read from the reading apparatus (such as that described in Patent Application EP-A-0652530 by this Applicant), being operatively linked to the microprocessor which is to process the light scattered from the illuminated code to calculate the value of the distance to which the code is located and select, through appropriate circuitry, an optimum illumination configuration from a plurality of preset illumination configurations. Examples of optimal illumination configurations versus distance are given in Table 1.

DISTANCE (cm)	MAIN ILLUMINATOR	AUXILIARY ILLUMINATOR
$d < 2$	OFF	FULL POWER
$2 < d < 4$	OUTER LEDS: FULL POWER INNER LEDS: OFF	FULL POWER
$4 < d < 7$	OUTER LEDS: FULL POWER INNER LEDS: MEDIUM POWER	MEDIUM POWER
$d > 7$	FULL POWER	OFF

Table 1

In a second embodiment, not shown, the operational parameter indicating specific conditions of the reading operation is the code light intensity outline; the reading apparatus includes here an envelope extractor, of a type known, which is operatively linked to a microprocessor, itself arranged to compare the outline of light intensity being scattered from the code with a reference outline in order to select an optimum illumination configuration from

002250 04902E60

a plurality of preset illumination configurations. In particular, with the emission angle of each LED being known, the reading area can be divided into n imaginary regions of action, one for each LED; the average level of
5 the code light intensity is detected on each of said regions and compared with a target average level. The microprocessor, based on the n difference values thus obtained and while taking account of the extent that each LED can contribute to also illuminate adjacent regions of
10 action, will then decide as to whether the light intensity contribution of each of them should be increased or decreased by increasing or decreasing the supply current.

In the preferred embodiment of the invention, the reading apparatus includes a means of amplifying the electric
15 signal generated by the detection means 4, means of converting the amplified electric signals to digital signals, and a microprocessor arranged to process the digital signals and attempt to decode the read code (all of which are not shown because conventional). In this
20 embodiment, the operational parameter indicating specific conditions of the reading operation is the number of unsuccessful decoding attempts; thus the microprocessor will, based on this number, decide on which of the LEDs 6 and 7 to activate in order to produce an optimum
25 illumination configuration.

Preferably, the amplifying means is a controlled gain type, that is capable of varying the electric signal amplification level, and the converting means comprises a main digitalizer having a preset sensitivity and an
30 auxiliary digitalizer having a higher sensitivity than the main digitalizer.

The operation of the reading apparatus of this invention will now be described in relation to its preferred embodiment.

35 The optical code is illuminated to define a first read

scan; light scattered from the code is picked up, through the objective lens 9, on the detection means 4 to generate an electric signal representing the light image scattered back from the code. This signal is then amplified and
5 converted to a digital signal by the main digitalizer; the digitalized signal is subsequently supplied to the microprocessor for further processing.

In particular, the microprocessor is arranged to use a control algorithm effective to control the turning on of
10 individual LEDs in the first and second arrays of light sources, such that an optimum illumination configuration can be selected from a plurality of preset illumination configurations to suit specific conditions of operation and, therefore, allow the bar code to be decoded. The
15 algorithm is constructed to take into account the fact that a remote reader is involved having two arrays of light sources and two digitalizers.

To this aim, two preset configuration modes are provided for the two illuminators, and two configuration modes for
20 the two digitalizers. The preset configuration modes for the two illuminators are as follows:

- a primary configuration mode wherein all the LEDs 6 of the main illuminator are supplied with a constant current same as the nominal current, and the LEDs 7 of the
25 auxiliary illuminator are turned off;

- a secondary configuration mode wherein the outward LEDs 61 of the main illuminator are supplied with a constant current which is one half the nominal current, the inward LEDs 62 are turned off, and the LEDs 7 of the auxiliary
30 illuminator are supplied with a constant current same as the nominal current.

In operation, the microprocessor will decide as to whether the first or the second of said configurations modes should be activated, switching from the current one to the other,

according to the number of unsuccessful attempts made to decode the code. As for the main and the secondary digitalizers, these are both kept always active, to each time digitalize the same analog signal coming from the amplifying means; however, the microprocessor will only process the output signal from one of them, switching from the current one to the other, according to the number of unsuccessful attempts at decoding the code.

Starting from a default configuration mode denoted by A in the diagram of Figure 6 (which configuration is considered to represent an optimum for high dynamic range signals and medium-to-long distances), wherein the main digitalizer and the illuminators in the primary configuration mode are used, the control algorithm programmed into the microprocessor will provide a drive strategy for the illuminators and the digitalizers directed to enable the code to be read correctly. In particular, this strategy consists of carrying out two operation cycles, respectively a restricted cycle and a standard cycle. During the restricted operation cycle, the operation is switched from the starting configuration A to a second configuration mode C (regarded to be an optimum for low dynamic range signals and medium-to-long distances), wherein the auxiliary digitalizer and the illuminators in the primary configuration mode are used, and the other way round. During the standard operation cycle, the operation is switched from the starting configuration A to a third configuration mode B, same as the second configuration C, and then to a fourth configuration mode D (regarded to be an optimum for high dynamic range signals and short distances), wherein the main digitalizer and the illuminators in the secondary configuration mode are used, and ultimately to a fifth operation configuration mode E (regarded to be an optimum for low dynamic range signals and short distances), wherein the auxiliary digitalizer and the illuminators in the secondary configuration mode are used. The standard operation cycle is terminated by going

back to the starting operation configuration mode A.

The driving strategy for the illuminators and the digitalizers provided by this invention to have an optical code properly read will be discussed next.

- 5 The reading step starts from the starting configuration mode A. The optical code is, therefore, illuminated with the LEDs of the first array of light sources 6, and the analog electric signal detected is amplified and converted to a digital signal by the main digitalizer. The
10 digitalized signal is then supplied to the microprocessor which, before attempting to decode, will check if the number of transitions detected on the signal is larger or smaller than a predetermined value K (e.g., eight).

- The term "transition" is used in this specification and the
15 appended claims to indicate a switch between two different levels of brightness; for example, a transition would occur from a white element to a black element of a bar code, and vice versa.

- The above check is to verify that the processed signal does
20 represent an optical code. In fact, if the number of transitions is found very small, it is judged that the illuminated reading area contains no optical codes so that, rather than a decoding attempt, a new read scan would be made of preference. On the other hand, if the number of
25 transitions exceeds the predetermined value K, it is judged that the illuminated reading area does contain an optical code, and a decoding attempt is made.

- In the former instance, the microprocessor would instruct the acquisition of a new scan, iteratively repeating the
30 check for the number of transitions detected on the signal for a predetermined number j of times (e.g., five). If the check gives a negative result consecutively for a predetermined number j of times (and hence, with no decoding attempts being made), the microprocessor instructs

a change to the configuration mode C, carrying out the restricted operation cycle. On the other hand, each time that the check for the number of transitions gives a positive result, a decoding attempt is made, and if the
5 attempt is successful, the code decoding is indicated and preparation is made for reading another code; otherwise, the microprocessor instructs a change to the configuration mode B for carrying out the standard operation cycle. A change to the configuration B is also instructed where a
10 total number of decoding attempts greater than a predetermined number p (e.g., six) is made in the configuration mode A.

In the configuration modes C and B, the checking steps for the number of transitions that appear in the scan are
15 repeated iteratively, along with decoding attempts, if any, as described hereinabove.

The choice of the cycle to be performed is dependent on the fact that a switch in illumination configuration involves a glare effect, commonly known as "flashing", which may be
20 objectionable for the user. Accordingly, from the starting configuration A, a decision is made as to whether a restricted cycle or a standard cycle is to be performed on the basis of discriminating data: the occurrence of at least one unsuccessful decoding attempt (an event denoted
25 by the term BAD DECODING) in the starting configuration mode A. The absence of BAD DECODING events would indicate, in fact, that the number of transitions in the acquired signal is insufficient and rules out, with good probability, the existence near the reading apparatus of an
30 optical code which goes undecoded because of insufficient illumination; on the contrary, this is likely to be an indication of a code lying far away and/or having low contrast (a situation of low dynamic range of the signal). Under such conditions, performing the restricted cycle is
35 preferred, thereby avoiding the need to change the illuminator and the flashing effect that goes with it.

It should be noted that the detection of the discriminating data (the occurrence of at least one BAD DECODING event) when deciding on the cycle to be performed, is only effected on the signal from the main digitalizer (configuration A), which is far more reliable than the auxiliary digitalizer. Being more sensitive than the main digitalizer, the auxiliary digitalizer is quicker to detect dummy transitions (i.e., transitions due, for example, to the presence of objects of different colors, or differently illuminated and/or colored, in the field of view of the reading apparatus, rather than to the presence of any bar code).

The choice of switching between digitalizers in advance of the illuminators is dictated by the fact that the reading apparatus of the invention is specifically designed for remote reading, i.e. for reading distant codes. Thus, the missed decoding (BAD DECODING event) is first attributed to an insufficient dynamic range of the signal (as due to the code remoteness and consequent poor illumination, or to low contrast of the print), which is tentatively obviated by the use of a more sensitive digitalizer (the auxiliary digitalizer); in fact, it will be appreciated that in the above-outlined situation, switching to the auxiliary illuminator is of no avail. This change would only be effected where the switching of digitalizers yields unsatisfactory results, it being then justifiable to conclude that the code is in a close-by position. In this case, the main digitalizer is concurrently operated, the assumption being that, with a code in a close-by position, the illumination is sufficient; accordingly, a decoding attempt on a signal which contains the smallest possible amount of distortion (i.e., the signal from the main digitalizer) is to be preferred.

The operation goes back to the starting configuration mode A from configuration C, if alternatively:

- a decoding attempt has been successful;

- the check for the number of transitions detected in the signal gives a negative result consecutively for a predetermined number j of times without any decoding attempts being made;

- 5 - the total number of unsuccessful decoding attempts is greater than a predetermined number q (e.g., four).

The operation goes back to the starting configuration mode A from configuration B, if alternatively:

- a decoding attempt has been successful;
- 10 - the check for the number of transitions detected in the signal gives a negative result consecutively for a predetermined number j of times without any decoding attempts being made. On the other hand, if in configuration mode B the total number of unsuccessful decoding attempt
- 15 exceeds a predetermined number q (e.g., four), then the microprocessor instructs a change to the configuration mode D of operation.

- Preferably, the change to the configuration mode D is preceded by a step of varying the signal amplification
- 20 level (step AGC PULSE in the diagram of Figure 6). In particular, the microprocessor will effect a sort of amplifier gain reset by suddenly forcing a gain value equal to the maximum allowable value and then allowing it to evolve naturally back to the correct value. This will
- 25 obviate, on the one side, an inherently slow action of the amplifier when called upon to adjust the gain level upwards, and on the other side, provision of very high gain levels that the amplifier would be unable to attain naturally because they can lead to signal saturation. Such
- 30 high gain values might provide an adequate amplification of the signal in those instances where it is very low, thereby permitting digitalization.

In the configuration mode D, the steps of checking for the number of transitions in the scan, and any decoding

attempts, are repeated iteratively as described above.

From the configuration mode D, the operation goes back to the starting configuration A, when a decoding attempt is successful. If in the configuration mode D the total number of unsuccessful decoding attempts exceeds a predetermined number p (e.g., six), or if the check for the number of transitions detected in the signal gives a negative result consecutively for a predetermined number j of times, without any decoding attempts being made, the microprocessor instructs a change to the configuration mode E.

In the configuration mode E, the steps of checking for the number of transitions in the scan, as well as any decoding attempts, are repeated iteratively as previously described.

From the configuration mode E, the operation finally goes back to the starting configuration A (to begin a new cycle) after carrying out the AGC PULSE step, if alternatively:

- a decoding attempt is successful;
- the check for the number of transitions detected in the signal gives a negative result consecutively for a predetermined number j of times without any decoding attempts being made; or
- the total number of unsuccessful decoding attempts is greater than a predetermined number q (e.g., four).

It should be noted that the transitions from configuration A to configuration B, and from D to E, occur after six BAD DECODING events in configurations A and D, respectively, whereas the transitions from B to D, and from E to A, only occur after four BAD DECODING events in B and E, respectively. This will depend on the activation or deactivation of AGC PULSE. The effect of a sudden, artful modification of the gain value of the analog signal amplification stage makes itself felt through two or three

scans; in order for the stage to be restored to its normal amplification value, a sufficient number of scans must be completed.

- 5 More generally, the numbers of events, K, j, p, q, may not be the same for all of the configuration modes, A, B, C, D, E.; preferably, such number will be individually different for each of said configuration modes.

In the diagram of Figure 6, the process steps described hereinabove are designated as follows:

- 10 - NULL: is a variable which is updated each time that a new reading is carried out with no decoding attempts being made (accordingly, a NULL event will occur where the acquired scan contains an insufficient number of transitions for recognition as a bar code);
- 15 -BAD_DEC: is a variable which is updated each time that a decoding attempt is made (a BAD DECODING event will occur where the attempt is unsuccessful);
- GOOD DECODING: is an event that will occur where the decoding attempt is successful;
- 20 - solid line rectangles represent steps in which values are assigned for NULL and BAD_DEC variables:
- solid lines represent switches between configuration modes as brought about by BAD DECODING events;
- outlined lines represent switches between configuration modes as brought about by NULL events.
- 25

- In the method of this invention, the NULL variable is updated each time that a new reading is carried out, each time that a decoding attempt is made (regardless of whether successfully or unsuccessfully), and each time that a configuration switch occurs. The BAD_DEC variable is updated each time that a decoding attempt is made, and is reset each time that the operation goes back to the
- 30

2

CLAIMS

1. An optical code reading apparatus, comprising:
- a casing;
 - a reading window open into the casing;
- 5 - an illuminating means (3), housed within the casing, and arranged to act on an optical code to be read through the reading window;
- a detection means (4), housed within the casing and responsive to light scattered from the illuminated optical
- 10 code into the casing through the reading window;
- an objective lens (9) having an optical axis (Z), the objective lens being housed within the casing between the reading window and the detection means (4), and being located to pick up light scattered from the illuminated
- 15 optical code and project the picked-up light onto the detection means (4), wherein the detection means (4) comprises a plurality of light-sensitive elements (5a) capable of converting said light to electric signals representing the light image;
- 20 characterized in that the illuminating means (3) comprises a first array of light sources (6) which are active in a first illumination configuration, and at least a second array of light sources (7) which are active in at least a second illumination configuration different from the first.
- 25 2. An apparatus according to Claim 1, wherein the first array of light sources (6) comprises a plurality of light source pairs (61,62), each pair (61,62) in turn comprising respective light sources symmetrically arranged with respect to the optical axis (Z) of the objective lens (9)
- 30 and aligned along a substantially perpendicular direction to said optical axis (Z), said light sources lying in a first emission lay (X-Z) intersecting the optical axis (Z) and the light-sensitive elements (5a) of the detection

means (4).

3. An apparatus according to Claim 2, wherein the plurality of light source pairs (61,62) comprises a pair of outward sources (61) disposed in an offset position from the optical axis (Z) of the objective lens (9) by an angle α , and a pair of inward sources (62) disposed in an offset position from the optical axis (Z) of the objective lens (9) by an angle β , smaller than the angle α .
4. An apparatus according to Claim 3, wherein the angle α is in the range of about 15° to about 18°, and the angle β is in the range of about 3° to about 6°.
5. An apparatus according to Claim 1, wherein the detection means (4) comprises a linear CCD sensor (5).
6. An apparatus according to Claim 1, wherein the detection means (4) comprises a CCD matrix sensor.
7. An apparatus according to Claim 1, wherein the detection means (4) comprises a CMOS sensor.
8. An apparatus according to Claim 1, further comprising a means (10,11) for confining the light beam from the first array of light sources (6) within a predetermined reading area.
9. An apparatus according to Claims 3 and 8, wherein the means (10,11) for confining the light beam from the first array of light sources comprises a ring-shaped masking element (11) associated with the casing at the location of the reading window and having a substantially straight inward edge (12), set at an angle substantially equal to α with respect to the optical axis (Z) of the objective lens (9).
10. An apparatus according to Claims 2 and 8, further comprising a holder element (8) for the plurality of light source pairs (61,62) which is formed with respective seats

(6a) for said light sources, said seats (6a) having respective side walls (10) shaped to confine the light beam from each source within the predetermined reading area.

11. An apparatus according to Claim 2, further comprising a means for widening the emission angle of the light beam from the first array of light sources (6) along the direction of alignment of said first array of light sources, and narrowing the emission angle of the light beam from the first array of light sources (6) along the perpendicular direction to the first emission lay (X-Z).

12. An apparatus according to Claim 11, wherein the means for widening the emission angle of the light beam from the first array of light sources (6) along the direction of alignment of said first array of light sources and narrowing it along the perpendicular direction to the first emission lay (X-Z) comprises a pair of converging lenses (13) housed within the casing at symmetrical locations with respect to the optical axis (Z) of the objective lens (9), between the first array of light sources (6) and the reading window.

13. An apparatus according to Claim 1, wherein the second array of light sources (7) comprises a plurality of second light sources having a lower light intensity than the sources in the first array of light sources (6).

14. An apparatus according to Claims 2 and 13, wherein the second light sources are housed within the casing symmetrically with respect to the optical axis (Z) of the objective lens (9), so as to be aligned to one another in a second emission lay, different from the first one.

15. An apparatus according to Claim 14, wherein the second light sources are housed within the casing centrally with respect to the first array of light sources (6), and wherein the second emission lay is lower than the first emission lay (X-Z).

16. An apparatus according to Claim 1, wherein the first array of light sources (6) comprises two pairs of discrete plastics LEDs and the second array of light sources (7) comprises four SMD plastics LEDs.

5 17. An apparatus according to Claim 1, respectively comprising a means for measuring the distance of the optical code to be read from the reading apparatus, and a means for activating said first and at least second arrays of light sources (6,7) according to the distance measured.

10 18. An apparatus according to Claim 1, respectively comprising a means for detecting the light intensity outline of the light scattered from the optical code, a means for comparing this outline with a reference outline , and a means for activating said first and at least second
15 arrays of light sources (6,7) according to the difference between the detected outline and the reference outline .

19. An apparatus according to any of the preceding claims, further comprising a means for decoding the optical code.

20 20. An apparatus according to Claim 19, further comprising a means for activating said first and at least second arrays of light sources (6,7) according to the results of decoding attempts.

25 21. An apparatus according to Claim 20, wherein the means for activating said first and at least second arrays of light sources (6,7) comprises a microprocessor, the apparatus further including a means of amplifying the electric signals generated by the detection means and means of converting the amplified electric signals to digital signals to be delivered to the microprocessor.

30 22. An apparatus according to Claim 21, further comprising a means for varying the amplification level of the electric signals generated by the detection means.

23. An apparatus according to Claim 21, wherein the

converting means comprises a main digitalizer having a preset sensitivity, and an auxiliary digitalizer whose sensitivity is higher than that of the main digitalizer.

24. A method of reading an optical code by an apparatus
5 comprising a means of illuminating an optical code to be read and means of detecting light scattered from the illuminated optical code, which method comprises the following steps:

10 - a) illuminating an optical code to be read so as to define a read scan;

- b) picking up the light scattered from the illuminated optical code on the detection means;

- c) converting the picked-up light to electric signals representing the light image;

15 characterized in that step a) of illuminating the optical code in turn comprises the following steps:

- a1) acquiring an operational parameter indicating specific conditions of the reading operation;

20 - a2) activating, according to the acquired operational parameter, a first array and/or at least a second array of light sources so as to illuminate the code according to respective preset illumination configurations.

25 25. A method according to Claim 24, wherein said first array of light sources comprise a plurality of sources having a predetermined light intensity, and said at least a second array of light sources comprises a plurality of sources having a lower light intensity than said sources in the first array.

30 26. A method according to Claim 24, wherein step a1) of acquiring the operational parameter includes a step of measuring the distance of the code to be read from the reading apparatus.

27. A method according to Claim 24, wherein step a1) of acquiring the operational parameter includes the following steps:

- 5 - detecting a light intensity outline of the light scattered from the optical code;
- comparing said outline with a reference outline ;
- controlling the emissions from the light sources in the first and/or second arrays of light sources according to the difference between the detected outline and the
10 reference outline.

28. A method according to Claim 24, further comprising the following steps:

- d) amplifying the electric signals generated by the detection means;
- 15 - e) converting the amplified electric signals to digital signals by means of a digitalizer;
- f) carrying out an attempt of decoding the optical code; and
- f1) if said attempt gives a positive result,
20 indicating the decoded code and repeating the steps from a) to read a new code;
- f2) if said attempt gives a negative result, iteratively repeating for a predetermined number i of times the steps from a), while each time changing the
25 illumination configuration.

29. A method according to Claim 28, wherein step f) of carrying out an attempt of decoding the optical code is preceded by the following step:

- 30 - e1) examining the digitalized signals to detect the number of transitions contained therein and check if said

number is greater than or equal to a predetermined value K, and:

- e1a) if such check gives a positive result, carrying out step f);

5 - e1b) if such check gives a negative result, abandoning the scan under examination and iteratively repeating the steps from a) for a predetermined number i of times.

30. A method according to Claim 24, wherein step a) of
10 illuminating the optical code to be read is preceded by the following step:

- i) setting a first configuration mode by activating a main digitalizer having a preset sensitivity and the first array of light sources respectively.

15 31. A method according to Claim 30, wherein if the check in step e1) gives a negative result consecutively for a predetermined number j of times, the following step is carried out:

- e1b1a) switching to a second configuration mode by
20 activating, rather than the main digitalizer, an auxiliary digitalizer having higher sensitivity than that of the main digitalizer, and iteratively repeating the steps from a), to switch back to the first configuration mode if alternatively:

25 - a decoding attempt is successful;

- the check in step e1) gives a negative result consecutively for a number j of times;

- a number of unsuccessful decoding attempts is made which is greater than a predetermined number q.

30 32. A method according to Claim 30, wherein if the check in step e1) gives a negative result consecutively for a

predetermined number j of times and at least one decoding attempt has been unsuccessful, or a number of unsuccessful decoding attempts is made which is greater than a predetermined number p, the following step is carried out:

- 5 - e1b1b) switching to a third configuration mode by activating, rather than the main digitalizer, an auxiliary digitalizer having higher sensitivity than that of the main digitalizer, and iteratively repeating the steps from a), to switch back to the first configuration mode if
10 alternatively:

- a decoding attempt is successful;
- the check in step e1) gives a negative result consecutively for a number j of times.

33. A method according to Claim 32, wherein if in step
15 e1b1b) a number of unsuccessful decoding attempts is made which is greater than a predetermined number q, the following step is carried out:

- 20 - e1b1b1) switching to a fourth configuration mode by activating the main digitalizer and the second array of light sources and controlling the emission from the sources in the first array of light sources, and iteratively repeating the steps from a), to switch back to the first configuration mode if a decoding attempt is successful.

34. A method according to Claim 33, wherein if in step
25 e1b1b1) a number of unsuccessful decoding attempts is made which is greater than a predetermined number p, or the check in step e1) gives a negative result consecutively for a predetermined number j of times, the following step is carried out:

- 30 - e1b1b1a) switching to a fifth configuration mode by activating the auxiliary digitalizer and the second array of light sources and iteratively repeating the steps from a), to switch back to the first configuration mode if

alternatively:

- a decoding attempt is successful;
- the check in step e1) gives a negative result consecutively for a predetermined number j of times;

- 5 - a number of unsuccessful decoding attempts is made which is greater than a predetermined number q.

35. A method according to Claims 32 to 34, further comprising a step of varying the amplification level by suddenly forcing a predetermined maximum value before
10 respectively switching from the third configuration mode to the fourth one, and from the fourth and fifth configuration modes to the first one.

662250 64503660

ABSTRACT

The invention relates to an apparatus and a method for reading an optical code. The apparatus comprises a casing with a reading window; the casing comprises an illumination means acting through the reading window on an optical code to be read, a detection means responsive to light scattered from the illuminated optical code into the casing through the reading window, and an objective lens interposed between the reading window and the detection means, in a position to pick up the light scattered from the illuminated optical code and project this light onto the detection means. The detection means comprises a plurality of light-sensitive elements effective to convert the light to electric signals representing the light image. The apparatus is characterized in that the illumination means comprises a first array of light sources active in a first illumination configuration, and at least a second array of light sources active in at least a second illumination configuration different from the first one.

20

(Fig. 1)

6449269




FIG.1




FIG. 2







FIG. 3








FIG. 6

Declaration and Power of Attorney for Patent Application

Dichiarazione e procura ai fini della domanda di brevetto

Italian Language Declaration

Il sottoscritto inventore dichiara che:

La propria residenza, recapito postale e cittadinanza corrispondono a quanto indicato in calce, sotto la propria firma.

Ritiene di essere il primo ed unico inventore originale (se viene elencato in calce un solo nominativo) o il coinventore primo ed originale (se è elencato più di un nominativo) del oggetto rivendicato e per il quale il sottoscritto presenta domanda di brevetto. La invenzione in questione è chiamata

60200-44350

La sua descrizione è allegata alla presente Dichiarazione a meno che non sia spuntata la seguente casella:

Il _____
è stata depositata una domanda di brevetto statunitense numero o una domanda di brevetto internazionale PCT numero _____
che è stata modificata il _____
(se applicabile).

Il sottoscritto dichiara in oltre di aver letto e compreso il contenuto della descrizione identificata in precedenza, rivendicazioni comprese, come modificati dall'eventuale modifica summenzionata.

Il sottoscritto riconosce l'obbligo di rivelare informazioni essenziali ai fini della determinazione della brevettabilità ai sensi del Titolo 37, Codice dei Regolamenti Federali, § 1.56.

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

An apparatus and method for

reading an optical code

the specification of which is attached hereto unless the following box is checked:

☐ was filed on _____
as United States Application Number or PCT
International Application Number
_____ and was amended on
_____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56.

Italian Language Declaration

Il sottoscritto rivendica con la presente la priorità prevista dal Titolo 35, Codice degli Stati Uniti, § 119(e)-(d) o § 365(b) in relazione a qualsiasi domanda o domande estere di brevetto o certificato di inventore, o dal Titolo 35, § 365(a) degli stessi Codice in relazione a qualsiasi domanda internazionale PCT nella quale è designato almeno un paese diverso dagli Stati Uniti, i suddetti domande e certificati essendo elencati sotto, e, spuntando les seguenti caselle, ha anche identificato sotto qualsiasi domanda estera di brevetto o certificato di inventore, o domanda internazionale PCT, la cui data di deposito preceda quella della domanda per la quale è rivendicata la priorità.

Prior foreign application(s)

Domande Estere Anteriori

98830336.8

(Number)

(Numero)

EPO

(Country)

(Nazione)

(Number)

(Numero)

(Country)

(Nazione)

Il sottoscritto rivendica con la presente i benefici previsti dal Titolo 35, Codici degli Stati Uniti, § 119(e), in relazione a qualsiasi domanda o domande provvisorie degli Stati Uniti elencate sotto.

(Application No.)

(N° della domanda)

(Filing Date)

(Data di deposito)

(Application No.)

(N° della domanda)

(Filing Date)

(Data di deposito)

Il sottoscritto rivendica con la presente i benefici previsti dal Titolo 35, Codice degli Stati Uniti, § 120, in relazione a qualsiasi domanda o domande statunitensi, o dal Titolo 35, § 365(c) degli stessi Codice in relazione a qualsiasi domanda internazionale PCT nella quale sono designati gli Stati Uniti, i suddette domande essendo elencate sotto e, nella misura in cui l'oggetto di ciascuna rivendicazione di questa domanda non sia stato esposto nella domanda statunitense o internazionale PCT anteriore nel modo previsto dal primo paragrafo del Titolo 35, Codice degli Stati Uniti, § 112, riconosce l'obbligo di rivelare informazioni essenziali ai fini della determinazione della brevettabilità ai sensi del Titolo 37, Codici dei Regolamenti Federali, § 1.56, le quali diventino disponibili durante il periodo compreso tra la data di deposito della domanda anteriore e la data di deposito nazionale o internazionale PCT della presente domanda.

(Application No.)

(N° della domanda)

(Filing Date)

(Data di deposito)

(Application No.)

(N° della domanda)

(Filing Date)

(Data di deposito)

Con la presente, il sottoscritto dichiara veritiere tutte le affermazioni contenute in questa domanda in relazione alle proprie conoscenze e di ritenere vere tutte le affermazioni o informazioni presentate. Dichiaro inoltre che tali asserzioni sono state espresse nella piena consapevolezza che le dichiarazioni intenzionalmente false sono punibili con una multa, l'incarcerazione o entrambe, ai sensi della Sezione 1001 del Titolo 18 del Codice degli Stati Uniti e che tali dichiarazioni intenzionalmente false possono mettere a repentaglio la validità della domanda o di qualsiasi brevetto rilasciato in merito.

I hereby claim foreign priority under Title 35, United States Code, § 119(a)-(d) or § 365 (b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Priority Not Claimed
Diritto di priorità non rivendicato

1 June 1998

(Day/Month/Year Filed)

(Giorno/Mese/Anno di deposito)

☐

(Day/Month/Year Filed)

(Giorno/Mese/Anno di deposito)

☐

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below.

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

(Status)(patented, pending, abandoned)

(Stato)(concessione di brevetto, in corso di esame, abbandono)

(Status)(patented, pending, abandoned)

(Stato)(concessione di brevetto, in corso di esame, abbandono)

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Italian Language Declaration

PROCURA: Il sottoscritto inventore nomina con la presente il seguente avvocato o avvocati e/o agente o agenti al fine di istruire questa pratica e di condurre tutte le operazioni ad essa pertinenti presso l'Ufficio dei Brevetti e Marchi di Fabbrica: *(Elencare il nome ed il numero di matricola)*

John H. Mion, Reg. No. 18,879; Donald E. Zinn, Reg. No. 19,046; Thomas J. Macpeak, Reg. No. 19,292; Robert J. Seas, Jr., Reg. No. 21,092; Derryl Maxie, Reg. No. 23,063; Robert V. Sloan, Reg. No. 22,775; Peter D. Olney, Reg. No. 24,513; J. Frank Osha, Reg. No. 24,625; Waddell A. Biggart, Reg. No. 24,861; Robert G. Mc Morrow, Reg. No. 19,093; Louis Gubinsky, Reg. No. 24,835; Neil B. Siegel, Reg. No. 25,200; David J. Cushing, Reg. No. 28,703; John R. Inge, Reg. No. 26,916; Joseph J. Ruch, Jr., Reg. No. 26,577; Sheldon I. Landsman, Reg. No. 25,430; Richard C. Turner, Reg. No. 29,710; Howard L. Bernstein, Reg. No. 25,665; Alan J. Kasper, Reg. No. 25,426; Kenneth J. Burchfiel, Reg. No. 31,333; Gordon Kit, Reg. No. 30,764; Susan J. Mack, Reg. No. 30,951; Frank L. Bernstein, Reg. No. 31,484; Mark Boland, Reg. No. 32,197; William H. Mandir, Reg. No. 32,156; Scott M. Daniels, Reg. No. 32,562; Brian W. Hannon, Reg. No. 32,778; Abraham J. Roener, Reg. No. 33,276; Bruce E. Kramer, Reg. No. 33,725; Paul F. Neils, Reg. No. 33,102; and Brett S. Sylvester, Reg. No. 32,765.



POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: *(list name and registration number)*

Inviare le corrispondenza a:

Send Correspondence to:
SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC
2100 Pennsylvania Avenue, N.W. Suite 800
Washington, D.C. 20037-3202

Telefonare a: *(nome e numero telefonico)*

Direct Telephone Calls to: *(name and telephone number)*

Nome e cognome dell'unico o del primo inventore	Full name of sole or first inventor
	Marc PIVA
Firma dell'inventore	Inventor's signature
	 Date Apr. 27 1999
Residenza	Residence
	I-61010 Maciano di Pennabilli (Pesaro)
Cittadinanza	Citizenship
	Italian
Recapito postale	Post Office Address
	Via Serra di Sopra 25
Nome e cognome dell'eventuale secondo coinventore	Full name of second joint inventor, if any
	Maurizio BIANCHI
Firma del secondo coinventore	Second inventor's signature
	 Date Apr. 27 1999
Residenza	Residence
	I-40126 Bologna
Cittadinanza	Citizenship
	Italian
Recapito postale	Post Office Address
	Via Innerio 23

(Fornire le stesse informazioni e le firme del terzo e degli ulteriori coinventori.)

(Supply similar information and signature for third and subsequent joint inventors.)